



HEAVY DUTY DEGREASER



PRODUCT DESCRIPTION:

CYCLONE CLEAN HEAVY-DUTY DEGREASER is designed to be used with both cold and heated water, high-pressure washers. Crafted by experts in the field, this degreaser quickly breaks down and safely removes exhaust soot, hydraulic fluids and fuel residue, oils, dirt, grease, waxes, polishing compounds, salts, soluble oils, drilling, and cutting compounds from the surface.

FEATURES:

- Effective with cold or hot water equipment
- Effective with oil/water separators
- Penetrates crevices, recesses, and hard-to-reach areas
- Provides a reliable and uniform cleaning

BENEFITS:

- Formulated with biodegradable ingredients
- Environmentally friendly formula promotes a cleaner and healthier working environment
- Non-flammable/non-combustible
- Strong chemistry for long duration use

WHAT IS IT:

CYCLONE CLEAN HEAVY-DUTY DEGREASER is a water-based product, designed to quickly remove grease, oils, and other contaminants from surfaces. It's specifically developed to be used with Cyclone Technology heated pressure cleaning equipment to provide efficient and thorough cleaning while minimizing the risk of damage to surfaces.

WHAT IT IS USED FOR:

It is highly effective in the removal of oil, grease and hydraulic fluids on concrete and asphalt surfaces. It can also be used effectively on equipment, steel, aluminum, titanium surfaces among others.

HOW IT WORKS:

It works by utilizing novel water-based chemistry to break down contaminants on surfaces. Surfactants enhance the cleaning process by reducing surface tension and allowing the cleaner to penetrate small crevices. Cyclone Technology full recovery equipment dislodges stubborn contaminants. High temperature and dwell time enhance the cleaning efficiency.



Application Guidelines:

Directions for PRE-SOAK HEAVY-DUTY DEGREASER:

- Dilute Degreaser 3:1 with water (3 parts water to 1 part degreaser). Spray area to be cleaned using a heavy-duty pump sprayer.
- Soak Time- After spraying soak for a minimum of 10-15 minutes prior to cleaning.
- Rinse using a pressure washer at 1000-3000 psi.
- Always flush return system at end of cleaning.

For Direct Tank Mixing in Pressure Washers:

- Use Dilutions based on PSI of equipment being used.
- Pre-wet surface to be cleaned with water.
- Always follow dilution schedule on label for PSI.
- Always flush the return system at the end of cleaning.

USE IT WITH THE FOLLOWING:



TR5000



CY210

SK2



CY5000

Specifications:

- | | |
|---------------------------------|--------------|
| • Readily Biodegradability | 100% |
| • Flammable/Combustible | No |
| • SCAQMD Certified | Yes |
| • Contains Terpenes | No |
| • Caustics | No |
| • pH @ Concentrate | 12.0-12.3 |
| • pH @ 1-3 Dilution | 11.0-11.9 |
| • Density lbs. /per gal | 8.34 lbs/gal |
| • Color/Characteristic | Clear/Liquid |
| • VOC SCAQMD 313.91 Concentrate | 47 g/l |
| • VOC SCAQMD 313.91 Diluted | 2:1 15 g/l |

Concentrated solution, superior cleaning
Defoaming agent
Low VOC's, no odor and no hazardous waste
Leaves no residue
Easy to mix and fast to use
Water-based solution
Light to heavy dirt-soil-oil is removed
Safe for the environment
Cost benefit in labor savings
No respirator required
Can safely be used on industrial equipment, engines and fleet vehicles

Directions: PRE-SOAK CLEANER
 Dilute Degreaser 3:1 with water (3 parts water to 1 part Degreaser). Spray area to be cleaned using a pressure pump sprayer.
 Soak Time- After spraying soak for a minimum of 10-15 minutes prior to cleaning.
 Rinse using a pressure washer (1000-3000 psi).
 Always flush return system at the end of cleaning.

For Direct Tank Mixing in Pressure Washers:
 Use Dilutions based on PSI of equipment being used.
 Pre-wet surface to be cleaned with water.
 Always follow dilution chart by PSI.
 Always flush the return system at the end of cleaning.

| PSI | MIXTURE | CLEANER |
|-------------|---------|---------|
| 500 - 1000 | 1 | 1 |
| 1000 - 2000 | 2 | 1 |
| 2000 - 3000 | 3 | 1 |
| 3000 + | 4 | 1 |

1 Gallons 3.78 L liters

Faster, Greener, Cleaner

Safety/Caution:

Rubber gloves are recommended to prevent drying of the skin. Goggles are recommended to protect eyes if splashing is expected. . When using product in steam cleaning and/or pressure washing applications wear a rain suit and boots to keep clothes dry. Harmful if swallowed. Avoid getting into eyes. If contact occurs, flush with running water. If irritation persists, get medical attention. May cause dryness of skin with prolonged use, wash hands with cold water and apply a hand lotion.



800-335-9695



www.cycloneclean.com



Cyclone Technology, LLC
 2424 S. 21st St., Phoenix, AZ 85034